




ABPI PANEL PRODUCTS


FOR INDUSTRIAL, AGRICULTURAL & COMMERCIAL APPLICATIONS

PANEL OPTIONS









TANK PANEL FOAM HAS SAW CUTS EVERY 4" PER 33" COVERAGE. TO ACHIEVE A TIGHTER BEND RADIUS, MORE SAW CUTS CAN BE ADDED. PLEASE CONTACT ABPI'S TECHNICAL DEPARTMENT FOR MORE INFORMATION.

TECHNICAL INFORMATION

SQUARE EDGE PANEL

PANEL THICKNESS: 1 1/2"

SQUARE EDGE 47-1/2" COVERAGE PANEL WIDTH:

LAP JOINT PANEL

1 1/2" - 2" - 2 1/2" - 3" - 4" - 6" PANEL THICKNESS:

PANEL WIDTH: LAP JOINT 33" COVERAGE TANK PANEL 33" COVERAGE

MINIMUM: 4' PANEL LENGTH:

MAXIMUM: 40'

OTHER LENGTHS AVAILABLE ON REQUEST *

SKIN MATERIALS: **ALUMINUM**

GALVANIZED GALVALUME **PAINTED**

STAINLESS STEEL ON REQUEST *

SKIN THICKNESS: 26 GA. STANDARD

24 GA. STANDARD ALUMINUM

OTHER GAUGES AVAILABLE ON REQUEST *

INSULATION: **POLYURETHANE**

2.5 LBS./CU.FT. MINIMUM DENSITY:

R-VALUE: R 7.14 / INCH

FIRE TESTING IN ACCORDANCE WITH CAN/ULC S102-M88

FLAME SPREAD: 65 SMOKE DEVELOPMENT: 210

C.F.I.A. APPROVAL ON SELECTED PANELS (# A399)

WFIGHT CHART: IBS. / SQ.FT.

WEIGHT OF IT	200. / 34.11.							
SINGLE SKIN		PANEL THICKNESS						
SKIN MATERIAL	GA.	1.5"	2"	2.5"	3"	4"	6"	
ALUMINUM GALVANIZED GALVALUME PAINTED STAINLESS STEEL	24 26 26 26 26 26	0.6 1.3 1.2 1.2 1.1	0.7 1.4 1.3 1.3 1.2	0.9 1.5 1.4 1.4 1.3	1.0 1.6 1.5 1.5 1.4	1.3 1.8 1.7 1.7 1.6	1.9 2.2 2.1 2.1 2.0	
DOUBLE SKIN		PANEL THICKNESS						
CIZINI MATERIAL	CA.	4 5"	o"	2 5"	7"	4"	c"	

SKIN MATERIAL CA 15" 2" 25" 3" 4"	6"
SKIN MATERIAL GA. 1.5" 2" 2.5" 3" 4"	סן
ALUMINUM 24 0.9 1.0 1.5 1.2 1.4 GALVANIZED 26 2.2 2.3 2.4 2.5 2.7 GALVALUME 26 2.1 2.2 2.3 2.4 2.6 PAINTED 26 2.1 2.2 2.3 2.4 2.6 STAINLESS STEEL 26 1.9 2.0 2.1 2.2 2.4	1.8 3.1 3.0 3.0 2.8

* PLEASE CONTACT ABPI'S TECHNICAL DEPARTMENT FOR MORE INFO.

A BETTER PANEL INC. BOX 6165 4006 - 60th AVE. INNISFAIL, AB, T4G 1S8



www.abetterpanel.com PH.: 403-227-4545 FAX: 403-227-4535